




- Steel frame with ISO corner castings, sub frame, and "tread plate" decking
- · (2) sets fork pockets
- Patented folding "A" Frame, with front bale bar, can be lowered on to the deck for storage and transport
- (2) all steel, lockable storage boxes within body of deck for straps and ratchets, etc.
- Removable rollers for use during (PLS, LHS, Drops) loading/unloading
- (2) each retractable folding ISO Twistlocks (Front)
- (2) each hinged-lever ISO Twistlocks (Rear)
- (29) "D" rings restraints located on the side and end rails, rated @ 10,000 lb. capacity, SWL
- This Flatrack is designed with extra retractable twistlocks to carry the following:
 - A Standard 20' ISO Container
 - (1) Bicon or (2) Bicons coupled
 - (1) Tricon or (2-3) Tricons coupled
 - (2-4) Quadcons coupled
- · Complies with STANAG 2413, certified
- Protected under US Patent #: 5,799,585, RE38,076 E and other worldwide patents



20' x 8'0" Wide ISO Container on top of the 20' PLS Flatrack



9 High Stack of 20' PLS Flatracks in ISO Container Ship Transport Mode

Under license from Lock Nest LLC.

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	Length	Length ISO Locks Deployed	Width	Height "A" Frame (Erect)	Deck Height
Ft in	19' 10 1/2"	20' 9"	8' 0"	5' 3 17/64"	10"
Metric	6,058	6,325	2,438	1,607	254

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT
Lbs	3,800	32,450	36,250
Kgs	1,724	14,719	17,000

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

• 081016-R01

ISO 9001

