

## **Tricon 2-Side Expandable Container**





## STANDARD FEATURES

- Container walls expand on both ends to provide additional internal space
- Lightweight panels allow for easy deployment by two people with no tools required
- Deployable in rugged terrain without the need for leveling jacks
- · Self-adjusting steps
- · Insulated wall panels with R7 value
- · Four-way fork lift pockets
- (2) Personnel doors with 18" overhang above each
- Tan ext. paint or Customer's Color Choice (CC)

## **OPTIONAL FEATURES**

- Connecting couplers, (3) per Tricon (SB2341)
- · External storage box
- · Electrical and Lighting Package



101215-R02

## ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATES ISO STANDARD

TRANSPORT MODE	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft in	96.00"	73.75"	96.00"	86.25"	77.50"	73.50"	75.63"	33.75"
Metric	2,438	1,873	2,438	2,191	1,969	1,867	1,921	984

EXP. MODE	LENGTH		HEIGHT			WIDTH			
	Exterior	Interior	Ext. (Fixed)	Int. (Fixed)	Int. (Exp)	Ext. (Fixed)	Ext. (Exp)	Int. (Fixed)	Int. (Exp)
Ft in	258.50"	218.50"	96.00"	86.25"	81.63	77.50"	64.50"	73.50"	69.50"
Metric	6,566	5,550	2,438	2,191	2,073	1,969	1,638	1,867	1,765

**ISO 9001** 

CERTIFIED QUALITY
MANAGEMENT SYSTEM

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	TRANS. CUBIC CAPACITY	EXP. CUBIC CAPACITY
Lbs	3,930	6,070	10,000	270.30 Cu.Ft.	801.40 Cu.Ft.
Kgs	1,783	2,753	4,536	7.65 Cu.M.	22.69 Cu.M.

GSA Advantage!™

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

Phone: 856 . 303 . 1101