



20' 2-Side Expandable, Folding Shelter



Transport Mode



Deployed Mode



STANDARD PRODUCT FEATURES

- 20' x 8' ISO Container, 9-high stacking
- Doors on both ends
- 20-minute set up time by 2 men
- Expanding section is self supporting to allow deployment while on a truck or trailer
- Power Input Panel (PIP) for connection to commercial power source or generator
- Standard electrical package, electric winch, fluorescent lighting - 9 each 48" twin bulb
- CFC-free Polyurethane foam insulation
Thermal Value: R-12 walls and R-18 roof
- Highly mobile, can be shipped via major transport systems
- Leveling jack set, 4 each
- Optional Packages Available

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

Transport Mode	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft in	19' 10"	19' 1"	8' 0"	6' 10"	8' 0"	6' 0"	6' 6"	3' 2"
Metric	6,058	5,810	2,438	2,083	2,438	1,828	2,000	952

Deployed Mode	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft in	19' 10"	19' 1"	8' 0"	6' 10"	21' 0"	20' 7"	6' 6"	3' 2"
Metric	6,058	5,810	2,438	2,083	6,413	6,280	2,000	952

20'	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	CUBIC CAPACITY Transport Mode	CUBIC CAPACITY Deployed Mode
Lbs	10,300	7,275	17,600	776 Cu.Ft.	2,683 Cu. Ft.
Kgs	4,700	3,300	8,000	22 Cu.M.	76 Cu. M.

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

