

# 20' L x 32' W x 18' H Collapsible Re-Deployable Shelter 4B4C



### **FEATURES**

- · Lightweight, collapsible shelter that can be stacked 4-high to make a 20' ISO module 8' high for transport
- Designed to meet military requirements for rapid deployment
- 1 truck delivery
- · Collapsible end walls and one side wall
- (2) levels of floor space 20' x 32' each:
  (4) SB3893.7.CRS-B (middle units, stacked 2-high)
  (4) SB3893.7.CRS-C (end units, stacked 2-high)
- Two ways to egress from each level
- (2) aluminum stairs/walkway for upper level or roof access
- Durable, non-slip, waterproof interior floor coating

### TRANSPORTABILITY

(8) shelters on a truck or C-130 Aircraft

# CONSTRUCTION

- · Unit, 9'0" high, can be stacked 4-high (2) CRS-B and (2) CRS-C
- 3" urethane foam sandwiched between galvanized steel construction for hardened personnel shelter protection
- Corrosion resistant side panel (inner/outer) sheets and frame
- · Smooth sides and pre-painted
- 20,000 lbs. tare weight

# ELECTRICAL

- · (2) overhead lights
- · Flush-mounted, (2) sockets and (1) switch
- · Plug and play electric mounted to interior ceiling, all levels

U.S. Patent No. 9.108.758







# **ELECTRICAL** (Cont'd)

- 120/208 VAC breaker panels with
- (2) 20A breakers on each level, includes 120 VAC & (8) USB charging outlets on each level
- · 4' LED light fixtures, (8) per level and (4) switches per level

### INSULATION

- · Rigid CFC-free polyurethane foam insulation
- Heat transmission coefficient roof/floor: 0.38 W/mK
- Heat transmission coefficient walls: 0.60 W/mK
- R22 insulation
- Combination heating/cooling

Note: Optional features available upon request



ิ ค ง

helter 4B4C

022516-R02

# ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	LENGTH		HEIGHT		WIDTH (per floor)	
	Exterior	Interior	Exterior	Interior	Exterior	Interior
Ft in	19' 10 1/2"	19' 3/4"	9' 0"	8' 1/2"	32'	31' 3 1/8"
Metric	6,058	5,810	2,743	2,451	9,754	9,528

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

1 Sea Box Drive, East Riverton, NJ 08077-2004

Phone: 856 . 303 . 1101

Fax: 856 . 303 . 1501

Email: sales@seabox.com

www.seabox.com