

20' x 8' 6" High Domino Type (4) with Flush Folding Endwalls



STANDARD PRODUCT FEATURES

- · End wall folding flush with the floor
- · Lashing beams set into the floor
- · Removable end walls for vehicle loading
- · Spare parts available worldwide
- · Commonly and readily available for leasing
- · Seven units fold into 8' 6"
- · 9 high stacking at 24,000 Kgs

TYPICAL LASHINGS AND INTERFACING

- · Stanchions: 4 sockets per side size 85mm
- Lashing bars: 8 x 5000kg per side, 2 per end
- Cross floor lashing: 4 x 2m per floor each with:
 6 x 5000kg lashing bars, 8 x 2m chocking slots
- · Floor: 45mm softwood planks 6mm gaps
- · Fork pockets: 115 x 360mm
- Twistlocks: 1 piece forged lift element, 30 degree stainless steel detent
- · Header locks: 2 per end semi-automatic
- Corner locking: hammer locked conical pin
- · Counterbalancing: leaf spring
- · Removable ends: optional use as ramps
- · Approvals: ABS, LRS, BV, UIC, CSC, TCT



The end walls fold flush with the floor. Seven units fold into 8ft6in. This is one of 20 patent designs exclusive to CSA licensees.

The 20ft Type (4) has a flat panelled end wall which folds directly on top of the base. When folded it can be used as a 20ft platform flat. The base includes four full width cross floor lashing recesses which will support chocking blocks, lashing chains, straps etc. Recesses are open to the ground for self cleaning. The end wall can be removable for vehicle loading. The floor surface is virtually continuous through recess zones.

Worldwide Spare Parts

As worldwide leaders in flatrack technology, the all important spare parts are available as they have been for more than 20 years.

Patents

Please do not encourage copying of the patented structures and components.

021119-R00

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	EXTERNAL				
	Length	Width	Height	Folded	
Ft in	19' 10 1/2"	8' 0"	8' 6"	1' 2 1/2"	
Metric	6,058	2,438	2,591	370	

	INTERNAL				
	Wall Panel to Panel	Mid-Post to Post	Platform Width	Height at Post	
Ft in	19' 9 23/32"	18' 6"	7' 3 41/64"	7' 4"	
Metric	6,038	5,638	2,226	2,233	
	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	LOAD OVER 2m	
Lbs	6,060	73,300	79,360	44,092	
Kgs	2,750	33,250	36,000	20,000	



ISO 9001



MANAGEMENT SYSTEM



ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS