

40ft Domino Type (4) with Flush Folding Endwalls



STANDARD PRODUCT FEATURES

- · End wall folding flush with the floor
- · 50 ton gross or more
- · Lashing beams set into the floor
- · Removable end walls for vehicle loading
- · Spare parts available worldwide
- · Commonly and readily available for leasing
- · Four units fold into 8' 6"
- · 7 high stacking at 30,480 Kgs

OPTIONAL PRODUCT FEATURES

- · Sling lift points
- · Post extensions

TYPICAL LASHINGS AND INTERFACING

- · Stanchions: 6 sockets per side size 85mm
- Lashing bars: 12 x 5000kg per side, 2 per end
- Cross floor lashing: 4 x 2m per floor each with:
 6 x 5000kg lashing bars, 8 x 2m chocking slots
- Floor: 45mm softwood planks 6mm gaps
- · Gooseneck tunnel: both ends
- · Fork pockets: 115 x 360mm
- Twistlocks: 1 piece forged lift element, 30 degree stainless steel detent
- · Header locks: 2 per end semi-automatic
- · Corner locking: hammer locked conical pin
- · Counterbalancing: leaf spring or coil
- · Removable ends: optional use as ramps
- Approvals: ABS, LRS, BV, UIC, CSC, TCT



This is a heavy duty flatrack where the end walls fold flush with the floor. Four units fold into 8ft6in. This is one of 20 patent designs exclusive to CSA licensees.

The 40ft Type (4) has a flat panelled end wall which folds directly on top of the base. When folded it can be used as a 40ft platform flat. The base includes four full width cross floor lashing recesses which will support chocking blocks, lashing chains, straps etc. Recesses are open to the ground for self cleaning. The end wall can be removable for vehicle loading. The floor surface is virtually continuous through recess zones.

Worldwide Spare Parts

As worldwide leaders in flatrack technology, the all important spare parts are available as they have been for more than 20 years.

Patents

Please do not encourage copying of the patented structures and components.

030401-R40

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	EXTERNAL				
	Length	Width	Height	Folded	
Ft in	40' 0"	8' 0"	8' 6"	2' 1 1/2"	
Metric	12,192	2,438	2,591	648	

	INTERNAL				
	Wall Panel to Panel	Mid-Post to Post	Platform Width	Height at Post	
Ft in	39' 11 1/2"	38' 2 47/64"	7' 3 41/64"	6' 5"	
Metric	12,180	11,652	2,226	1,955	
	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	LOAD OVER 2m	
Lbs	10,800	99,430	110,230	56,000	
Kgs	4,900	45,100	50,000	25,400	



CERTIFIED QUALITY
MANAGEMENT SYSTEM



ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS