

40' FLATRACK with Ramp on One End Wall ISO Cargo Container



PRODUCT FEATURES

STANDARD FEATURES

- One end wall folds outward to serve as a ramp with the additional wheel ramps for ease of loading trucks
- Ramp end wall is counter balanced for 2-man operation
- Storage pockets are provided for wheel ramps
- End wall folding flush with the floor
- · 50-ton gross or more
- · Spare parts available worldwide
- Designed for vehicles with 10,000 lbs. cap. (per axle) on ramp

TYPICAL LASHINGS AND INTERFACING

- Lashing: 6 x 5000kg lashing bars
- · Floor: 45mm softwood planks, 6mm gaps
- · Goosneck Tunnel: both ends
- · Fork pockets: 115 x 360mm
- Twistlocks: 1 piece forged lift element, 30 degree stainless steel detent
- · Header locks: 2 per end semi-automatic
- · Corner locking: hammer locked conical pin
- · Approvals: ABS, LRS, BV, UIC, CSC, TCT

000000-R00

ISO 9001



ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

40' FLATRACK	LENGTH		HEIGHT		WIDTH		HEIGHT COLLAPSED
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height
Ft in	40' 0"	39' 11 1/2"	8' 6"	6' 5"	8' 0"	7' 11"	2' 1 1/2"
40' FLATRACK	TARE WEIGHT		PAYLOAD		GROSS WEIGHT		7-HIGH STACKING
Lbs	11,500		98,730		110,230		60,000 Gross Weight

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

Phone: 856 . 303 . 1101