# 20' FLATRACK With Ramp on Both End Walls







## PRODUCT FEATURES

### STANDARD FEATURES

- · Both end walls fold outward to serve as a ramp with the additional wheel ramps for ease of loading trucks
- · Ramp end walls are counter balanced for 2-man operation
- · Storage pockets are provided for one set of wheel ramps
- Both end walls folding flush with the floor
- · 30-ton gross weight
- · Spare parts available worldwide
- · Designed for vehicles with 10,000 lbs. cap. (per axle) on both ramps
- Standard Marine Paint (Color: RED)

### TYPICAL LASHINGS AND INTERFACING

- · Floor: 45mm softwood planks, 6mm gaps
- · Fork pockets: 115 x 360mm
- · Twistlocks: 1 piece forged lift element, 30 degree stainless steel detent
- · Header locks: 2 per end semi-automatic
- · Corner locking: hammer locked conical pin
- · Approvals: ISO + CSC

NSN #: 8150-01-565-9039

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD							
20' FLATRACK	LENGTH		HEIGHT		WIDTH		HEIGHT COLLAPSED
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height
Ft in	19' 10 1/2"	19' 6"	8' 6"	7' 5 1/2"	8' 0"	7' 11"	1' 2 1/2"
20' FLATRACK	TARE WEIGHT		PAYLOAD		GROSS WEIGHT		9-HIGH STACKING
Lbs	6,700		68,260		74,960		48,000 Gross Weight

CONTRACT # GS-02F-0024P GSA Advantage!™

**CERTIFIED QUALITY** MANAGEMENT SYSTEM

**ISO 9001** 

052621-R00

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS