

20ft X 8ft Diesel / Electric Refrigerated **ISO Cargo Container**



STANDARD PRODUCT FEATURES

- · Aluminum, steel or sides
- · Double full opening swing doors on one end
- · Forklift pockets (on some 20' units)
- · Aluminum T-grade floors
- · Most refrigerated machinery features electrical supply as follows: 208/230, 380/460 Volts AC, 3 phase, 50 or 60 cycle
- Temperature range from -20°F to 70°F



000000-R00

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD FOR NINE (9) HIGH STACKING

| | . , | | | | | | | |
|--------|-------------|------------|----------|------------|----------|----------|--------------|-------|
| | LENGTH | | HEIGHT | | WIDTH | | DOOR OPENING | |
| | Exterior | Interior | Exterior | Interior | Exterior | Interior | Height | Width |
| Ft in | 19' 10 1/2" | 18' 2 1/2" | 8' 0" | 6' 10 1/2" | 8' 0" | 7' 4" | 6' 10 1/2" | 7' 4" |
| Metric | 6,058 | 5,550 | 2,438 | 2,096 | 2,438 | 2,235 | 2,096 | 2,235 |

| | TARE WEIGHT | PAYLOAD | GROSS WEIGHT | CUBIC CAPACITY |
|-----|-------------|---------|--------------|----------------|
| Lbs | 5,970 | 61,230 | 67,200 | 918 Cu. Ft. |
| Kgs | 2,708 | 27,772 | 30,480 | 26 Cu. M. |

ISO 9001:2008



ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS