45' X 9'6" Dry Freight ISO Cargo Container





STANDARD PRODUCT FEATURES

- · Corrugated steel sides, and roof
- · 14 gauge locking steel double end swing doors
- 1 1/8" thick marine plywood floors, forklift tested to 16,000 lbs per 44 square inches
- · Wall tie down steel lashing rings, 6,000 lbs. cap. each
- · Front corner post tie downs
- Door corner post tie downs = restraint system, shoring slot will support 2" x 6" lumber
- · Vents, (2) each

OPTIONAL PRODUCT FEATURES

- · Manifest box (2) each
- · Adjustable shelving brackets (12) sets
- · Decking and shoring beams (36) each

ISO 9001:2008

000000-R00



ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD FOR NINE (9) HIGH STACKING

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft in	45' 0"	44' 5 3/4"	9' 6"	8' 10 1/16"	8' 0"	7' 8 1/2"	8' 5 3/4"	7' 8 1/16"
Metric	13,716	13,557	2,896	2,694	2,438	2,350	2,585	2,338

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	CUBIC CAPACITY
Lbs	10,210	56,990	67,200	3,040 Cu. Ft.
Kgs	4,631	25,849	30,480	86.1 Cu. M.

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

Phone: 856 . 303 . 1101

EXTERNAL LENGTH 13716 (45), 4