

STANDARD PRODUCT FEATURES

- Aluminum, steel, or sides
- · Double full opening swing doors on one end
- Aluminum T-grade floors
- Most refrigerated machinery features electrical supply as follows: 208/230, 380/460 Volts AC, 3 phase, 50 or 60 cycle
- Temperature range from -20° F to 70° F

030216-R01

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD FOR NINE (9) HIGH STACKING

	LENGTH		HEIGHT		WIDTH			DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Ex	terior	Interior	Height	Width
Ft in	40' 0"	38' 0 3/4"	8' 6"	7' 3 5/8"	8	3' 0"	7' 5 5/8"	7' 6 1/2"	7' 5 5/8"
Metric	12,192	11,602	2,591	2,226	2	,438	2,276	2,299	2,276
		TARE WEIGHT		PAYLOAD	GROSS WEIGH		OSS WEIGHT	CUBIC CAPACITY	
Lbs		9,590		57,610		67,200		2,076 Cu. Ft.	
Kgs		4,350		26,130		30,480		58.8 Cu. M.	

ISO 9001



CONTRACT # GS-02F-0024P

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

1 Sea Box Drive, East Riverton, NJ 08077-2004

Phone: 856 . 303 . 1101

Fax: 856 . 303 . 1501 | E

Email: sales@seabox.com

www.seabox.com