

SFRS Generator Set "Clip On" Type (3 Plug)



STANDARD PRODUCT FEATURES

- The "clip-on" generator set is designed to clip on to the front frame of a refrigerated container. The water cooled diesel generator can provide continuous (single voltage) electrical power to intermodal refrigerated containers.
- · This unit is self contained with an integral 122 U.S. gallon (537 liter) fuel tank combined with engine, generator, battery and all operating controls.
- Power Output: 15kW, 18.7kva, (33 hp) @ 1800 rpm
- · Voltage Output: 230V, 3 phase, 46A @ 60Hz
- · Container clip-on to top header with pins
- · All steel frame with integral 122 gallon fuel tank
- · Solid-state battery charger
- · Electrostatic coated tube and fin radiator
- · 12V DC maintenance-free battery
- · CEE-17 female outlet receptacle with circuit breaker
- · This unit is designed for quick installation to the side frame of the container and connect up to 3 SFRS containers.
- · Warranty standard 2 years, complete genset

- · Kubota 134 cubic inch (2.2 liter) 4 cylinder water-cooled direct injected engine
- · Lima-Mac 460V AC, 15kW generator
- · 460V Receptacle CEE-17, 460VAC 32 amps, Carrier P/N 22-01561-00





Connect up to 3 SFRS Containers

| | DIMENSIONS | | |
|---------|------------|-----------|-------|
| | Length | Height | Depth |
| Ft. in. | 7' 8" | 3' 6 5/8" | 2' 1" |
| Metric | 2,337 | 1,083 | 635 |

| | Tare Weight without Fuel | Tare Weight with 122 Gallon Tank |
|-----|--------------------------|----------------------------------|
| Lbs | 1,675 | 3,746 |
| Kgs | 760 | 1,699 |

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS



090209-R00

ISO 9001

