

Double Doors One Side (Type 1)
Tricon Dry Freight ISO Cargo Container

PRODUCT FEATURES


STANDARD FEATURES

- Corrugated steel sides, roof and swing doors on one side
- · Heavy duty steel floor
- · Four- way fork lift pockets
- Wall tie down steel lashing rings, 4,000 lbs. cap. Each (28) total
- · Front corner post tie downs, (10) total
- Door corner post tie downs, (10) total = restraint system shoring slot will support 2" x 6" lumber
- Adjustable shelving brackets: (5) sets = (10)
 Vertical E-Track sections total
- · Vents, (2) each
- Exterior color OD Green # 34088 or Tan # 33446
- Interior color OD Green # 34088 or Tan # 33446

OPTIONAL FEATURES

- · Decking and Shoring Beams, (15) each
- · Connecting couplers, (3) per Tricon
- Connecting coupler storage bracket, (1) each
- · Manifest Box, (2) each with 1 set of Manuals





(3) TRICON CONTAINERS COUPLED TOGETHER TO FORM (1) 20' ISO MODULE

• 100815-R00

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

ALI NIII OON IAMILIO AKI MAKOTAOTOKID TO TIIL LATEOT IOO OTAKDAKS								
SB821.0	LENGTH (+0/-3)		HEIGHT (+0/-5)		WIDTH (+0/-5)		DOOR OPENING (+0/-4)	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft. in.	6' 5 9/16"	6' 3 25/64"	8' 0"	7' 5 9/64"	8' 0"	7' 7 23/32"	7' 1 43/64"	6' 1 25/32"
Metric	1,968	1,915	2,438	2,264	2,438	2,330	2,176	1,874
	TARE WEIGHT		PAYLOAD		GROSS WEIGHT		CUBIC CAPACITY	
Lbs.	2,600		12,300		14,900		356 Cu. Ft.	
Kgs.	1,179		5,579		6,759		10.09 Cu. M.	

ISO 9001



MANAGEMENT SYSTEM



ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS