

Double Doors Both Ends (Type 5)



SB825_0 Tricon Dry Freight ISO Cargo Contai Double Doors Both Ends (Type 5)

ler

(3) TRICON CONTAINER'S COUPLED TOGETHER TO FORM (1) 20' ISO MODULE

STANDARD FEATURES

- LOWEST TARE WEIGHT and LARGEST CUBIC CAPACITY for any Tricon Type 5
- Full-width cargo doors on both ends, (swing out a full 270 deg. For ease of loading)
- Four way fork lift pockets 4.0"H x 14.5"W x 34.73" center line spacing
- · Relief notches in all 4 bottom rails, (8) total
- Wall tie down steel lashing rings, 4,000 lbs. cap. each (20) total
- Door corner post tie downs, (20) total = restraint system shoring slot will support 2" x 6" lumber
- Floor tie down steel lashing rings, 4,000 lbs. cap. each (8) total
- · Interior marking 1/2" high stamped owner's code SN#
- · Vents, (2) each
- · Connecting couplers, (3) per Tricon
- · Connecting coupler storage bracket, (1) each
- Adjustable shelving brackets, (3) sets: (6) vertical E-Track sections total
- · Paint Non-CARC Green w/ 65% Zinc primer

PRODUCT FEATURES

- OPTIONAL FEATURES
- Decking and shoring beams, (6) each
- Composite shelving, (2) full size
- Rack and Cabinet systems
- · Steel locking bar & security seal system
- Padlock protection box
- · Padlocks, (2) each
- · Opening and closing vents, (2) each
- · Manifet boxes, (2) each
- CARC paint
- · Paint, Tan or White exterior color
- Tectyl undercoating

NSN #: 8150-01-609-6513

012616-R01

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

SB825.0	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft. in.	6' 5 31/64"	5' 11 1/32"	8' 0"	7' 5 1/64"	8' 0"	7' 9 57/64"	7' 1 3/64"	7' 8 1/8"
Metric	1,968	1,804	2,438	2,261	2,438	2,385	2,160	2,340
	TARE WEIGHT		PAYLOAD		GROSS WEIGHT		CUBIC CAPACITY	
Lbs.	2,800		12,100		14,900		343 Cu. Ft.	
Kgs.	1,270		5,490		6,760		9.73 Cu. M.	

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

1 Sea Box Drive, East Riverton, NJ 08077-2004

Phone: 856 . 303 . 1101

Fax: 856 . 303 . 1501 | Email: sales@seabox.com

www.seabox.com

ISO 9001



contract # gs-02f-0024p Advantage!™