



One Full Side Opening 10' x 8' 6" Bicon Dry Freight ISO Cargo Container

## **PRODUCT FEATURES**

## **STANDARD FEATURES**

- · Corrugated steel sides and roof
- Steel floors, forklift tested to 16,000 lbs. per 44 square inches
- Tie down steel lashing rings, 4,000 lbs. cap. each
- · (4) way forklift pockets
- · Vents, (2) each
- · One double side door

## **OPTIONAL FEATURES**

- · Connecting couplers, (2) per Bicon
- · Connecting coupler storage bracket, (1) each
- · Manifest box, (2) each
- Heavy duty adjustable E-Track System, (4) sets
- · Decking and shoring beams, (16) each
- · Non-Absorbing Composite Shelves

100815-R00

## ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

| SB843.6 | LENGTH      |             | HEIGHT   |             | WIDTH        |             | DOOR OPENING   |             |
|---------|-------------|-------------|----------|-------------|--------------|-------------|----------------|-------------|
|         | Exterior    | Interior    | Exterior | Interior    | Exterior     | Interior    | Height         | Width       |
| Ft. in. | 9' 9 3/4"   | 9' 7 43/64" | 8' 6"    | 7' 11 3/64" | 8' 0"        | 7' 6 59/64" | 7' 7 1/16"     | 9' 5 57/64" |
| Metric  | 2,991       | 2,938       | 2,591    | 2,414       | 2,438        | 2,310       | 2,313          | 2,893       |
|         | TARE WEIGHT |             | PAYLOAD  |             | GROSS WEIGHT |             | CUBIC CAPACITY |             |
| Lbs.    | 3,460       |             | 23,000   |             | 26,460       |             | 579 Cu. Ft.    |             |
| Kgs.    | 1,570       |             | 10,430   |             | 12,000       |             | 16.38 Cu. M.   |             |

ISO 9001





ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS