

20' X 8' 6" Dry Freight ISO Cargo Container with 2 Roll-Up Doors



## **PRODUCT FEATURES**

## STANDARD FEATURES

- · 14Ga corrugated steel sides and roof
- (2) Roll-up doors with rain hood diverter and top draft seal. Each door has a sliding lock designed to accept a pad lock
- (1) Interior metal wall partition with welded header creating (2) interior storage spaces @ 8' x 9 1/2' wide
- (1) set forklift pockets
- 1 1/8" thick marine plywood floors, forklift tested to 16,000 lbs per 44 square inches
- · Wall tie down steel lashing rings
- · Tan exterior color

## **OPTIONAL FEATURES**

- · Turbine roof vents, fixed air flow vents
- Electrical lighting with hard wire connection
- · Interior shelving





021816-R01

## ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft in	19' 10 1/2"	19' 4 11/64"	8' 6"	7' 9 7/8"	8' 0"	7' 8 17/32"	7' 5 11/16"	7' 8 11/64"
Metric	6,058	5,897	2,591	2,382	2,438	2,350	2,278	2,341

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	CUBIC CAPACITY
Lbs	5,100	47,810	52,910	1,171 Cu. Ft.
Kgs	2,313	21,687	24,000	33.2 Cu. M.

ISO 9001





ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS