

20' x 8' Dry Freight ISO Cargo Container Double Doors Both Ends (Type 2)





Shown with optional SB3451 Universal Weapons Cabinets

STANDARD PRODUCT FEATURES

- Corrugated steel sides, roof, and swing doors on both ends
- (2) sets of forklift pockets, laden and unladen
- 1 1/8" thick marine plywood floors, forklift tested to 16,000 lbs. per 44 square inches
- Wall tie down steel lashing rings, 4,000 lbs. cap. Each, (24 total) tested at 6,000 lbs.
- Front corner post tie downs (10 total)
- · Fully prepped to accept weapons racks
- Door corner post tie downs (10 total) = restraint system shoring slot; will support 2" x 6" lumber
- · Vents, (2) each
- · Manifest box, (2) each
- · Shoring slot system behind cargo doors
- · Capable of secure storage and transport of Military Crew Serve Weapons
- Able to restrain (13) each, SB3451 Universal Weapons Rack for transport storage and rapid removal
- Adjustable, heavy-duty, aluminum decking/shoring beams 3,000 lbs. decking/vertical capacity 2,500 lbs. shoring/horizontal capacity
- · Includes ratchet style, wide logistics straps for safe transport of items
- Technical Manual
- Standard TAN / Conventional Paint System 905

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

SB862.6	LENGTH (+0/-6)		HEIGHT (+0/-5)		WIDTH (+0/-5)		DOOR OPENING (+0/-5)		
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width]
Ft. in.	19' 10 1/2"	19' 2 5/64"	8' 6"	7' 10 3/8"	8' 0"	7' 8 19/32"	7' 6 1/32"	7' 8 1/8"]
Metric	6,058	5,844	2,591	2,397	2,438	2,352	2,287	2,340	
	TARE WEIGHT		PAYLOAD		GROSS WEIGHT		CUBIC CAPACITY		
Lbs.	5,020		62,180		67,200		1,163 Cu. Ft.		G
Kgs.	2,277		28,203		30,480		32.94 Cu. M.		

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

020416-R02

ISO 9001



CONTRACT # GS-02F-0024P

Email: sales@seabox.com

www.seabox.com

1 Sea Box Drive, East Riverton, NJ 08077-2004 | Ph

4 | Phone: 856 . 303 . 1101

-

Fax: 856 . 303 . 1501 | Email: sales(