


Two Full Side Opening 20' X 8' 6" Dry Freight ISO Cargo Container





PRODUCT FEATURES

STANDARD FEATURES

- · Corrugated steel ends + bifold swing doors on both sides
- (2) sets of forklift pockets, laden and unladen
- 1 1/8" thick marine plywood floors, forklift tested to 16,000 lbs per 44 square inches
- · Wall tie down steel lashing rings, 6,000 lbs. cap. each
- · Corner post tie downs
- · Floor recessed tie downs
- · Vents, (2) each

OPTIONAL FEATURES

- · Manifest box (2) each
- · 383 Green exterior CARC paint

100815-R00

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

SB892.6	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft. in.	19' 10 1/2"	19' 6 11/32"	8' 6"	7' 5 3/16"	8' 0"	7' 4 47/64"	7' 17/32"	19' 5" 25/32
Metric	6,058	5,952	2,591	2,265	2,438	2,254	2,147	5,938
	TARE WEIGHT		PAYLOAD		GROSS WEIGHT		CUBIC CAPACITY	
Lbs.	TBD		TBD		67,200		1,074 Cu. Ft.	
Kgs.	TBD		TBD		30,480		30.4 Cu. M.	

ISO 9001





ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS