# SEA BOX® 40' Intermodal Warehouse System (IWS)







## STANDARD PRODUCT FEATURES

- An inter-connectable, all-steel, cargo-carrying platform and intermodal warehousing system
- IWS can be slid in and out of standard ISO shipping containers, or transported on a flatbed truck or trailers
- IWS can be stacked loaded two high for transportation. potentially doubling shipping capacity
- · IWS can be stacked unloaded 4 high inside a 40' ISO Container
- · IWS can be stacked up to 4-high for warehousing or nested up to 15-high when not in use
- IWS reduce guarantine risk as laden platforms are containerized and secure, removing the need to shrink wrap cargo
- IWS provide a platform to facilitate ergonomic loading of operational Stores/Field Installation Work Packages (FIWP)
- Slider pads can carry more weight but won't damage container flooring

- · (1) set of side laden fork pockets
- (1) set of rear end fork pockets
- (2) Shoring bar locking mechanism, one at each rear side corner
- · 1" Thick heavy duty side rail tie down bars
- (2) Corner post stoppers at front end, one at each front
- · (2) Vertical rollers, two at each front side corner
- · (6) Corner fittings on curbside top rail, plus (6) on curbside bottom rail
- (6) Corner fittings on roadside top rail, plus (6) on roadside bottom rail
- (24) Total corner fittings
- · Deck surface designed to carry (2) 20' IWS end to end or (1) 20' IWS centered

## **OPTIONAL PRODUCT FEATURES**

- · 4 IWS legs at various heights for optimizing container space when stacking IWS
- IBC, semi-automatic twist locks are available

### ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	Length	Width	Height
Ft in	39' 5 7/32"	7' 6 3/8"	15 15/16"
Metric	12,020	2,296	404.5

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT
Lbs	11,023	55,115	66,138
Kgs	5,000	25,000	30,000

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

ISO 9001

062717-R00SS

